




## POLIWET TECH GOLD IMPRESS DUO

### *technical data sheet*

| DESCRIPTION  | APPLICATION   | FEATURES   |
|--|---|--|
| <p>A miniroll of non-woven material made of woodpulp and PET fibers soaked with cleaning solution, ready to be used.</p> | <p>Specifically designed for printing presses equipped with automatic blanket systems that do not have water and solvent distribution devices. Usable also in all the other automatic cleaning systems by deactivating the distribution device.</p> | <ul style="list-style-type: none"> <li>Specifically designed to both clean rubber blankets and the impression cylinders with a rough surface (the compact structure of Non-Woven have a low fiber peeling off).</li> <li>Developed for conventional Inks and UV</li> <li>Suitable for conventional blankets only</li> <li>Not for use with EPDM rubber blankets</li> </ul> |
|                                        |   |  |

### PHYSICAL AND MECHANICAL PROPERTIES OF THE DRY NON-WOVEN MATERIAL

| Property                   |                          | Test method   | Unit             | Nominal values |
|----------------------------|--------------------------|---------------|------------------|----------------|
| <b>Colour</b>              |                          | -             | -                | White          |
| <b>Weigth</b>              |                          | EDANA 40.3-90 | g/m <sup>2</sup> | 65             |
| <b>Nominal thickness</b>   |                          | EDANA 30.5-99 | mm               | 0.22           |
| <b>Tensile strength</b>    | <i>Machine Direction</i> | EDANA 20.2-89 | N/5cm            | 185            |
|                            | <i>Cross Direction</i>   |               |                  | 80             |
| <b>Elongation at break</b> | <i>Machine Direction</i> | EDANA 20.2-89 | %                | 20             |
|                            | <i>Cross Direction</i>   |               |                  | 60             |

### MECHANICAL PROPERTIES OF THE IMPREGNATED ROLL

| Property                                    | Test method   | Unit  | Nominal values |
|---|---------------|-------|----------------|
| <b>Tensile strength (Machine direction)</b> | EDANA 20.2-89 | N/5cm | 160            |

### STORAGE

Shelf-life: 6 months  
 Store away from heat and UV light.

*The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.*

T452 Rev.01n120/06/2023

*The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.*

*T452 Rev.01n120/06/2023*