




POLIWET TECH GOLD UV/B

technical data sheet

DESCRIPTION	APPLICATION	FEATURES
<p>A miniroll of non-woven material made of woodpulp and PET fibers soaked with cleaning solution: in quantity metered to guarantee the perfect wetting of the roll, ready to be used.</p> 	<p>Specifically designed for printing presses equipped with automatic blanket systems that do not have water and solvent distribution devices. Usable also in all the other automatic cleaning systems by deactivating the delivery system.</p>	<ul style="list-style-type: none"> Developed for all conventional and UV Inks Suitable for hybrid blankets, rollers and membranes

PHYSICAL AND MECHANICAL PROPERTIES OF THE DRY NON-WOVEN MATERIAL

Property		Test method	Unit	Nominal values
Colour		-	-	White
Weigth		EDANA 40.3-90	g/m ²	65
Nominal thickness		EDANA 30.5-99	mm	0.22
Tensile strength	<i>Machine Direction</i>	EDANA 20.2-89	N/5cm	185
	<i>Cross Direction</i>			80
Elongation at break	<i>Machine Direction</i>	EDANA 20.2-89	%	20
	<i>Cross Direction</i>			60

PROPERTIES OF IMPREGNATED ROLL

Property	Test method	Unit	Nominal values
Tensile strength (Machine direction)	EDANA 20.2-89	N/5cm	160

STORAGE

Shelf-life: 6 months
 Store away from heat and UV light.

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.

T518 Rev.01nl 28/04/2023