



POLICHEMICAL ADHESIVE REMOVER

technical data sheet

DESCRIPTION	APPLICATION	FEATURES
Cleaning solution for cylinders	Utilized to remove adhesive and dirt residues from cylinders for varnishing plates of printing machines	<ul style="list-style-type: none"> Suitable for removing water-based and solvent-based adhesives High cleaning power Not inflammable

INSTRUCTIONS OF USE
Distribute a uniform layer preferably using a wipe or a sponge, then clean using a wet wipe or sponge.

PHYSICAL AND CHEMICAL PROPERTIES

Property	Test method	Unit	Nominal values
Colour	-	-	Colourless
Boiling point	-	°C	162
Density	-	g/cm ³	0.90
Water solubility	-	-	Soluble

STORAGE

Please keep the tank in a safe place at a temperature in the range 4-30 °C.

SHELF LIFE 12 MONTHS

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.

T497 Rev.01 nl 04/10/2022